

XAMPP Setup

Windows:

Download the portable Zip of the current version (at the time of this writing: 7.1.7)

<https://sourceforge.net/projects/xampp/files/XAMPP%20Windows/>

Extract the 'xampp' folder suggesting to use C:/ as the target folder.

Remove the Semicolon in front of the line

```
;extension=php_sockets.dll
```

inside of xampp/php/php.ini

Linux:

Download the installer of the current version (at the time of this writing: 7.1.7)

<https://sourceforge.net/projects/xampp/files/XAMPP%20Linux/>

And run it.

Folder link setup

Add an entry to xampp/apache/conf/extra/httpd-xampp.conf

(On Linux this should be /opt/lampp/apache/conf/extra/httpd-xampp.conf)

```
...
<IfModule alias_module>
    ...
    Alias /bahn "<PATH TO YOUR GIT>/code/website"
    <Directory "<PATH TO YOUR GIT>/code/website">
        AllowOverride AuthConfig
        Require local
        ErrorDocument 403 /error/XAMPP_FORBIDDEN.html.var
    </Directory>
</IfModule>
```

Accessing the Website

After the setup you can run xampp-control inside the xampp folder and start apache or directly run 'apache_start' inside this folder.

Now you can open <http://localhost/bahn/>